

SOLDERPRO™ 100

Specifications	
Length: W/Cap	233 mm (9.2 in)
W/Soldering tip	215 mm (8.5 in)
Weight (when gas-filled)	142 g
Approximate temperature soldering tip	250~500°C (480~950°F)
Torch	1300°C (2400°F)
Gas container capacity	20 ml
Operating capacity (one gas filling)	120 min. at mid setting

Packing		
Item	PRO-100	PRO-100K
Packing (Inner Box/Carton)	12 / 48	12 / 24
Packaging	Blister/ Card	Tool Case W/ Color Box
Master Carton (L x W x H cm)	44.5x42.7x33.6	58.2x32.7x38.8
CU.FT.	2.3'	2.6'
N.W. (kg)	13.0	15.5
G.W. (kg)	14.2	17.5



PRO-100

PRO-100K

SOLDERPRO™ 100
30W-100W POWER RANGE

Cordless Butane Products At The Leading Edge

Automatic Ignition Portable Multi-function Heat Tool

Applications:

- Automotive and truck repairs
- Aviation service and repair
- Electrical components
- Environmental splicing
- Infield repairs
- Jewelry repair
- Loosen rusted nuts and bolts
- Maintain switch panels
- Sensitive IC boards
- Shrink tubing
- Soften window caulking
- Solder circuit boards
- TV cable systems
- Repair television sets, meters, switch boards

Features:

- Equivalent to a power range 30-100 Watt.
- Cordless, simple, safe operation anywhere.
- Ready to use 15 seconds after ignition.
- Tank fuel capacity for 120 minutes operation.
- No cords, can be used anywhere.
- No electrical interference.
- Comes with soldering tip and protective cap.



30W-100W POWER RANGE

SOLDERPRO™ 100

Economy Auto Ignition model with great performance, feel and cosmetics.

Basic Tips



CT-01 1.6mm Conical
CT-02 2.4mm Chisel
PS-9 Hot Knife
PS-10 Heat Blower
S-30 Deflector

Patents Pending
Worldwide

Colors:

