

SOLDERPRO™ 70

Specifications	
W/Cap	220 mm (8.7 in)
Length: W/Soldering tip	190 mm (7.5 in)
W/blow torch tip	172 mm (6.8 in)
Weight (when gas-filled)	76 g
Approximate temperature soldering tip	210~450°C (410~850°F)
Torch	1300°C (2400°F)
Gas container capacity	20 ml
Operating capacity (one gas filling)	120 min. at mid setting

Packing		
Item	PRO-70	PRO-70K
Packing (Inner Box/Carton)	12 / 72	12 / 24
Packaging	Blister/ Card	Tool Case W/ Clam Shell
Master Carton (L x W x H cm)	44.5x39.7x30.9	54.2x30.9x56.4
CU.FT.	1.9'	3.3'
N.W. (kg)	7.5	9.7
G.W. (kg)	9.5	11.8



SOLDERPRO™ 70

25W-80W POWER RANGE

Cordless Butane Products At The Leading Edge

Any-Time, Any-Where No Electric Required Gas Soldering Iron

Applications:

- Electrical/Electronic Circuit Repair
- Light Plumbing
- Jewelry, Eyeglass Frame Repair
- Model Building
- Arts and Crafts
- Dental Wax Corrections
- Thawing Frozen Locks
- Install Heat Shrink Tubing
- Install Heat Shrinkable Connectors
- Cut foam & plastics
- Caulterize rope ends

Features:

- Equivalent to a power range of 25-80 watts.
- Cordless, simple, safe operation anywhere.
- Ready to use 20 seconds after ignition.
- Tank contains fuel for 120 minutes of operation.
- No cords, can be used anywhere.
- No electrical interference.
- Comes with soldering tip and protective cap.



25W-80W POWER RANGE



SOLDERPRO™ 70

The standard manual ignition multi-function for engineers and technicians.
25W-80W equivalent electrical power.

Basic Tips



Patents Pending
Worldwide

Colors:

